



TECHNICAL DATA SHEET

DSC-0042-010



Product part	Materials
Drum	HDPE
Handle	HDPE
Lid	HDPE
Gasket	EPDM

Capacity	Liters	US Gallons
Brimful	42	11.10
When closed	42	11.10

Hazardous material information	
Hazardous material type	Solids
Packaging group	I – II – III
UN marking	UN/1H2/X51/S/--/NL/CURTEC 1239
Maximum gross mass (kg)	X=51



Weight	Grams	Ounces
Drum	1675	59.08
Handles	90	3.18
Lid	598	21.09
Gasket	30	1.06
Total	2393	84.41

Weight tolerance

All products have a tolerance of $\pm 4\%$ of the initial weight mentioned on this data sheet

Dimensional tolerances	%
Height	± 2.5
Diameter	± 1.5

Wall thickness	mm
Minimal wall thickness	≥ 1.8
Nominal wall thickness	≥ 1.8

Colors	Color code	PMS references
Drum*	White 004	/
Lid*	Red 402	199 C
Handle	Black 101	/

* Other colors available on request

Product identification	Drum	Lid
Manufacturer ID	Bottom	--
Product code	Bottom	--
Recycle logo / Material type	Bottom	Inside
Date clock	Bottom	Inside
UN-mark	Side wall	--
Food logo	Bottom	--
Material track clock	Bottom	--
CFR49-mark	Bottom	--

Other information

Maximum filling temperature is 70°C/ 158°F

Contents must have cooled to 30°C/ 86°F before containers can be closed and stacked

DoC available on request

UN certificate available on request

MVTR declaration available on request

Watertightness declaration available on request

User manual available on request

All drums can be made tamper evident with application of compact seal # 7800

